## **Chaparral Energy Monitor Well Construction Diagram Legal Description** Well # MW - 22 Quarters \_\_SW-SW-SE Section 13 Township 27N Range 05E1 WELL COVER / CASING PROTECTOR 8 5/8" steel casing FROM <u>+3'</u> TO <u>2'</u> ground level -SURFACE SEAL & PAD Concrete FROM +3' TO 2'ANNULAR SEAL Neat Cement WELL CASING 4" sch 40 PVC FROM 2' TO 132' FROM +2' TO 150'FILTER PACK SEAL Bentonite Chips FROM 132' TO 138' FILTER PACK Sand 10 - 20 Coarse SCREEN 4" sch 40 PVC Factory Slotted - .020 inch FROM 190' TO 228' FROM <u>150'</u> TO <u>170'</u> Bottom Cap 4" sch 40 PVC bottom cap FROM <u>170'</u> TO <u>170.5'</u> Backfill Bentonite Chips FROM 180' TO 250' Associated Environmental Industries, Corp P.O. Box 5306 Norman, Ok. 73070 (405)360-1434 Office / (405)360-1480 Fax Email: robert@aei-corp.co TOTAL DEPTH OF WELLBORE \_\_260' www.aei-corp.com 7.25" Borehole